
















Bravo is a premium cushioned sports and wellness flooring designed for modern day requirement of a floor that is heavy duty but soft enough for a comfortable and jerk free workout in a gym, sports court or a fitness centre. The high strength wear layer takes care of the heavy loads, the 'impregnated Glass Fibre Tissue' reinforcement provides a very high dimensional stability and lay flat properties to the product in any weather conditions. The densely compact cushioned base layer absorbs the jerks and also adds to the acoustical property of the floor.

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	SYMBOLS	TEST METHOD	RESULTS 4.50 MM	RESULTS 6.50 MM
THICKNESS		EN 426	4.50 MM	6.50 MM
ROLL DEMENSION		EN 426	2 mtr x 15 linear mtr	2 mtr X 15 linear mtr
TOTAL WEIGHT		EN 430	3.3 KG /SQ.	4.3 KG/SQ
THICKNESS OF WEAR LAYER		EN 429	0.50 MM	1.00 MM*
DIMENSIONAL STABILITY		EN 434	≤0.10%	<0.10%
RESIDUAL INDENTATION AFTER STATIC LOAD		EN 433	≤0.40 MM	< 0.40 MM
FLEXIBILITY		EN 435	20 MM MANDREL, PASSED	20 MM MANDREL PASSED
ABRASION RESISTANCE		EN 660-2 EN 649	WEAR GROUP P	WEAR GROUP P
SURFACE SPREAD OF FLAME		BS 476 PART 7	CLASS 1	CLASS 1
FIRE PROPAGATION		BS 476 PART 6	(I)=10.8 } CLASS "O", (II)=1.7	(I) = 10.8 } CLASS "O", (II) = 1.7
HYGIENE			TEST RESULT DEMONSTRATES THAT IT INHIBITS GROWTH OF MICROBES	TEST RESULT DEMONSTRATES THAT IT INHIBITS GROWTH OF MICROBES
COLOUR FASTNESS TO DAY LIGHT		ISO 105-BO2	>BLUE WOOL STANDARD 5	>BLUE WOOL STANDARD 5
SLIP RESISTANCE		DIN 51130	R 9	R 9
BEARING A CASTOR CHAIR		EN 425	SUITABLE/CONTINUOUS USE	SUITABLES/CONTINUOUS USE
RESISTANCE TO CHEMICALS		EN 423	NO VISIBLE CHANGE	NO VISIBLE CHANGE
SOUND ABSORPTION		ISO 140-8 EN ISO 717-2	Δ LW = 18db	ΔLW = 24db
PERFORMANCE CLASSIFICATION		EN 685	33, 34	33, 34
SURFACE PROTECTION			PUR	PUR

RECOMMENDATION FOR INSTALLATION

Wonderfloor sheet must be allowed to relax for 24 hours in room temperature between 18° C and 27° C prior to installation. Vinyl rolls are suitable for laying on any surface such as concrete, steel wooden floors etc. provided the sub-floor is even, hard and dry. Damp floors should be dried before the commencement of laying. Before installation, the base floor must be thoroughly clean, dry and free from grease & grit. Wonderfloor recommends use of Fevicol SR 998, Fevicol SR 505 or any other equivalent rubber/acrylic based adhesive of similar type.

MAINTENANCE

Do's: • The surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution • Prevent point load indentation by covering your furniture legs with rubber stopper caps • To remove stubborn stains, rub the affected area immediately with a soft coir brush or fine steel wool soaked in a warm soap solution • Scuff marks on the floor can be removed with little application of diesel • Use door coir or suitable mats to minimize accumulation of dust on Wonderfloor vinyl flooring • Use water to remove any chemical spill on flooring.

Don'ts: • Do not use any strong detergent, harsh cleaning agent or dry steel wool • Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn marks on the floor • Do not drag any heavy object or furniture on the flooring to avoid scratches on the floor.

For institutional/bulk enquiries, please e-mail : mkt@rmgpoly.com
or call : +91 9711200510

For export enquiries, please e-mail : info@rmgpoly.com or call : +91 9873138885



ISO 9001-2008
Certificate No. 01-100058473

RMG POLYVINYL INDIA LIMITED

Registered Office : UGSR 4, Ansal Plaza, Sector 1, Vaishali Ghaziabad 201 010, (U.P) INDIA
Tel.: +91 120-4284802/803/804/805/806, Fax: +91 11 66173679, E-mail: info@rmgpoly.com

Regional Offices : • Ahmedabad: +91 9377262959 • Bangalore: +91 9341263704 • Bhubaneswar: +91 9337423999
• Chennai: +91 9380353335 • Guwahati: +91 8822021287 • Hyderabad: +91 9533791422
• Indore: +91 9827791420 • Kolkata: +91 8820568222 • Kochi: +91 9349191423 • Lucknow: +91 9026708007
• Mumbai: +91 9323675979 • Pune: +91 9595191421 • Patna: +91 8252110100 • Raipur: +91 9827791419

www.wonderfloor.com

WONDERFLOOR is the registered Trade Mark of RMG Polyvinyl India Limited